LS592 Balitza Micro

Bollard & Pathway



The LS592 is the smallest version of the Balitza series. It is constructed from 316 marine grade stainless steel with Lumascape's proprietary **ElectroPolishPlus™** process to give a long life to the surface finish providing excellent corrosion resistance in harsh environments such as coastal locations. It is a compact accent luminaire, utilizing a low voltage halogen lamp to create low level lighting effects.




LS592 Balitza Micro

Specifications

Lamp	20 W max	Halogen Bi-pin / QT12 (G6.35)						
IP Rating	IP65							
Construction	316 marine g	316 marine grade stainless steel						
Installation Type	Surface mou	Surface mount						
Ambient Operating Temperature	32 °F to 122	°F (0 °C to +50 °C)						

Any luminaire can become hot - take care with appropriate use and placement



LS592				293				07
LAMP Description	Wattage	Base	Voltage	Code	HEAD TYPE	Code	INPUT VOLTAGE	Code
Halogen Bi-Pin / QT12	, , , , , , , , , , , , , , , , , , ,		12 V	293	Apex	H	12 V AC, 50 Hz	07 ⁽¹⁾
	20 11 114	.,		230	Level	F	(1) Requires remote transformer.	



Brisbane Technology Park, 18 Brandl Street, Eight Mile Plains, QLD 4113, Australia © +61 7 3854 5000 | ≞ +61 7 3854 5001 | ा sales@lumascape.com.au

